

TYPE FM4005-W LOT NO G50451329

Dimension of Body			Dimension of lead pad			
Tag Nbr	Length	Width	Height	Length	Width	Height
1	4.92	2.49	2.05	1.19	1.45	0.15
2	4.93	2.48	2.08	1.24	1.48	0.12
3	4.92	2.48	2.06	1.21	1.48	0.15
4	4.92	2.5	2.07	1.22	1.49	0.15
5	4.91	2.48	2.06	1.18	1.47	0.15
6	4.94	2.48	2.06	1.23	1.45	0.15
7	4.91	2.48	2.05	1.18	1.47	0.13
8	4.95	2.48	2.08	1.21	1.49	0.15
9	4.92	2.48	2.03	1.18	1.49	0.13
10	4.95	2.5	2.04	1.2	1.49	0.14
11	4.95	2.48	2.06	1.18	1.5	0.15
12	4.95	2.48	2.05	1.23	1.48	0.14
13	4.93	2.48	2.05	1.2	1.48	0.15
14	4.9	2.48	2.08	1.18	1.49	0.15
15	4.95	2.48	2.06	1.23	1.48	0.12
16	4.92	2.49	2.05	1.2	1.46	0.15
17	4.94	2.48	2.07	1.24	1.48	0.14
18	4.9	2.5	2.05	1.2	1.49	0.13
19	4.92	2.48	2.08	1.22	1.48	0.15
20	4.93	2.48	2.06	1.18	1.49	0.14
21	4.93	2.48	2.06	1.2	1.48	0.13
22	4.91	2.49	2.08	1.21	1.48	0.15
23	4.93	2.49	2.08	1.22	1.49	0.15
24	4.95	2.49	2.05	1.19	1.48	0.15
25	4.95	2.49	2.07	1.21	1.48	0.12
26	4.92	2.49	2.06	1.23	1.47	0.14
27	4.94	2.48	2.07	1.22	1.48	0.13
28	4.93	2.49	2.08	1.19	1.48	0.15
29	4.95	2.48	2.07	1.2	1.49	0.15
30	4.92	2.5	2.08	1.2	1.48	0.15
31	4.93	2.48	2.06	1.25	1.49	0.13
32	4.92	2.49	2.05	1.24	1.49	0.15
33	4.93	2.48	2.08	1.19	1.49	0.15
34	4.92	2.48	2.05	1.25	1.49	0.14
35	4.95	2.48	2.05	1.2	1.5	0.12
36	4.93	2.48	2.08	1.2	1.49	0.15
37	4.93	2.5	2.05	1.22	1.49	0.12
38	4.92	2.48	2.06	1.23	1.49	0.12
39	4.92	2.48	2.08	1.24	1.48	0.15
40	4.93	2.49	2.07	1.19	1.49	0.15
41	4.95	2.48	2.06	1.21	1.49	0.13
42	4.95	2.49	2.08	1.23	1.49	0.15
43	4.93	2.48	2.05	1.19	1.49	0.12
44	4.91	2.48	2.05	1.21	1.48	0.13
45	4.93	2.48	2.08	1.2	1.49	0.14
46	4.94	2.49	2.05	1.21	1.49	0.15
47	4.92	2.48	2.06	1.22	1.49	0.15
48	4.92	2.5	2.06	1.2	1.49	0.15
49	4.93	2.48	2.08	1.24	1.49	0.15
50	4.93	2.48	2.05	1.18	1.49	0.15

MIN	4.900	2.480	2.030	1.180	1.450	0.120
MAX	4.950	2.500	2.080	1.250	1.500	0.150
AVG	4.930	2.485	2.063	1.209	1.484	0.141
STD DEV	0.0140	0.0071	0.0133	0.0204	0.0103	0.0114
CPK	8.82	14.39	6.22	4.74	7.01	1.81



