

SURFACE MOUNT FAST SWITCHING DIODE ARRAY

Features

- * Fast Switching Speed: max. 50ns
- * Continuous Reverse Voltage: max. 200V
- * Repetitive Peak Reverse Voltage: max. 250V
- * Repetitive Peak Forward Current: max. 1A
- * Small Surface Mount Package
- * For General Purpose Switching Applications
- * High Conductance
- * P/N suffix V means AEC-Q101qualified, e.g: BAS21TWW
- * Halogen-free


SOT363



Top View

Mechanical Data

- * Case: SOT363
- * Case Material: Molded Plastic, "Green" Molding Compound, UL Flammability Classification Rating 94V-0
- * Moisture Sensitivity: Level 1 per J-STD-020
- * Terminals: Matte Tin Finish annealed over Alloy 42 leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208 ③
- * Orientation: See Diagram
- * Weight: 0.009 grams (approximate)



Top View
Internal Schematic

Maximum Ratings (@T_A = 25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V _{RM}	250	V
Peak Repetitive Reverse Voltage	V _{RRM}	250	V
Working Peak Reverse Voltage	V _{RWM}		
DC Blocking Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	177	V
Forward Continuous Current (Note 5)	I _{FM}	200	mA
Non-Repetitive Peak Forward Surge Current	I _{FSM}	@ t = 50µs	10
		@ t = 100µs	8
		@ t = 10ms	2

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 5)	P _D	300	mW
Thermal Resistance Junction to Ambient Air (Note 5)	R _{θJA}	417	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150	°C

Electrical Characteristics (@T_A = 25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 6)	V _{(BR)R}	250	—	V	I _R = 100µA
Forward Voltage	V _F	—	1.05	V	I _F = 100mA I _F = 200mA
		—	1.25		
Reverse Current (Note 6)	I _R	—	100	nA	V _R = 200V
			100	µA	V _R = 200V, T _J = +150°C
Total Capacitance	C _T	—	5	pF	V _R = 6, f = 1.0MHz
Reverse Recovery Time	t _{rr}	—	50	ns	V _R = 6V, I _F = 5mA

Notes: 5. Part mounted on FR-4 board with recommended pad layout
6. Short duration pulse test used to minimize self-heating effect.

RATING AND CHARACTERISTICS CURVES (BAS21TWV)




Figure 1 Power Derating Curve, Total Package




Figure 2 Typical Forward Characteristics, Per Element




Figure 3 Typical Reverse Characteristics, Per Element






Figure 4 Total Capacitance vs. Reverse Voltage, Per Element

Package Outline Dimensions




SOT363		
Dim	Min	Max
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Typ	
F	0.40	0.45
H	1.80	2.20
J	0	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.22
α	0°	8°
All Dimensions in mm		

Suggested Pad Layout



Dimensions	Value (in mm)
Z	2.5
G	1.3
X	0.42
Y	0.6
C1	1.9
C2	0.65

Marking Information



XJK = Product Type Marking Code
 YM = Date Code Marking
 Y = Year (ex: T = 2011)
 M = Month (ex: 9 = September)

Date Code Key

Year	2011	2012	2013	2014	2015	2016	2017	2018
Code	Y	Z	A	B	C	D	E	F

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

Ordering Information

Part Number	Case	Packaging
BAS21TW	SOT363	3000/Tape & Reel

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.